

JOINT ADHESIVE

Product Data Sheet



PRODUCT NAME	CODE	COLOUR
KG Brick Adhesive	A77	Grey

PRODUCT DESCRIPTION
High quality Polymer modified cementitious medium bed mortar for bedding all types of bricks and concrete blocks.

TECHNICAL DATA

DRY BULK DENSITY	JOINTING THICKNESS	BONDING STRENGTH
1.65 t/m ³	10 - 20 mm	≥ 0.6 N/mm ²
BINDER	COVERAGE	WATER FOR MIXING
Ordinary Portland Cement	3.5 m ² of wall per 40kg bag applicable to 100mm brick wall	23% ± 2% (9.2 Litre/bag)
OPEN TIME	SETTING TIME	POT LIFE
6 to 8 Minutes	5 Hours	3 Hours
PACKAGING	STORAGE	
40kg	6 Months	

INSTRUCTION FOR USE

SURFACE FOR USE

Ensure brick surfaces are sound, clean and free of any contamination.

MIXING

Mix the product thoroughly with approximately 23% by weight of clean water using an electric mixer with attached stirrer for 3 - 5 minutes, until a homogeneous mix is achieved.

APPLICATION

Apply mortar onto brick surfaces using trowel. Bricks should be seated in proper position. Gently tap brick with trowel handle.

FIRE RESISTANCE

This product is non-combustible.

SAFETY PRECAUTION

This product contains cement additives and may cause irritation when in contact with skin or eyes. In case of any contact, wash thoroughly with clean water. If irritation persists, seek immediate medical attention.

DISCLAIMER:

All information contained herein is only intended to give a fair description of the products and their capabilities under such specific test conditions.

However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.



KG-MIX (M) SDN BHD (705033-K)

PT 14498, Persiaran BG Perdana 6, Taman Batu Gajah Perdana, 31550 Pusing, Perak.

Tel: +6(05) 3668323 | Fax: +6(05) 3668363 | Email: inquiry@kgmix.com