



PRODUCT NAME	CODE	COLOUR
KG Patching Compound	CPC	Grey
PRODUCT DESCRIPTION		
High quality polymer modified fast setting, shrinkage compensated thixotropic concrete patching / repair mortar. It's a characterized with a remarkably high bonding to the substrate even in thin application.		

TECHNICAL DATA

DRY BULK DENSITY	APPLICATION THICKNESS	COMPRESSIVE STRENGTH
1.3 t/m ³	Up to 25 mm	≥ 30 N/mm ²
BINDER	COVERAGE	WATER FOR MIXING
Ordinary Portland Cement	1.5 kg/m ² per mm thick	4.5 - 5.0 litre per bag
OPEN TIME	SETTING TIME	POT LIFE
Approx. 15 Mins at 25°C	Initial 1 Hour	1 Hour
PACKAGING	STORAGE	
20kg	6 Months	

INSTRUCTION FOR USE

SURFACE FOR USE

Surfaces to be applied on must be sound, clean and free from any contamination materials. Wet surface before application in hot and dry conditions.

MIXING

Mix the patching compound with approximately 4.5 to 5.0 litres of clean water. Thoroughly mix, preferably using an electric mixer with a stirrer attachment. Do not mix more material than can be used within 20 minutes.

APPLICATION

Apply the material firmly with steel trowel.

FIRE RESISTANCE

This product is non-combustible.

SAFETY PRECAUTION

This product contains cement additives and may cause irritation when in contact with skin or eyes. In case of any contact, wash thoroughly with clean water. If irritation persists, seek immediate medical attention.

DISCLAIMER:

All information contained herein is only intended to give a fair description of the products and their capabilities under such specific test conditions.

However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.



KG-MIX (M) SDN BHD (705033-K)

PT 14498, Persiaran BG Perdana 6, Taman Batu Gajah Perdana, 31550 Pusing, Perak.

Tel: +6(05) 3668323 | Fax: +6(05) 3668363 | Email: inquiry@kgmix.com