

LATEX ADDITIVE

Product Data Sheet



PRODUCT NAME	CODE	COLOUR
KG Admixture	MA10	Milky White

PRODUCT DESCRIPTION

A ready to use multi-purpose latex admixture designed to increase bonding and flexural strength of cementitious dry mix and site mix, suitable for use at dry or wet, internal or external areas.

- To improve bonding and flexural strength of repair mortar, cement renders and screed.
- As general purpose primer for floor and wall.
- For renders and cementitious slurry.

TECHNICAL DATA

KG THICK RENDER P33 + KG ADMIXTURE MA10

BONDING STRENGTH	COMPRESSIVE STRENGTH	FLEXURAL STRENGTH
$\geq 0.8 \text{ N/mm}^2$	$\geq 5 \text{ N/mm}^2$	$\geq 1.2 \text{ N/mm}^2$

KG ADMIXTURE MA10

DRY BULK DENSITY	PACKAGING	STORAGE
1.02 t/m ³	18 Litre	12 Months

INSTRUCTION FOR USE

MIXING

Mixing procedure is similar to that traditional mix except the replacement of water requirement by KG Admixture in full or partial. For Cement Sand Mortar - Either full or partly replacement of water with KG-Admixture MA10 mix to desired consistency.

FIRE RESISTANCE

This product is non-combustible.

SAFETY PRECAUTION

This product contains cement additives and may cause irritation when in contact with skin or eyes. In case of any contact, wash thoroughly with clean water. If irritation persists, seek immediate medical attention.

DISCLAIMER:

All information contained herein is only intended to give a fair description of the products and their capabilities under such specific test conditions.

However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.



KG-MIX (M) SDN BHD (705033-K)

PT 14498, Persiaran BG Perdana 6, Taman Batu Gajah Perdana, 31550 Pusing, Perak.

Tel: +6(05) 3668323 | Fax: +6(05) 3668363 | Email: inquiry@kgmix.com