TEXTURE COAT

Product Data Sheet



PRODUCT NAME	CODE	COLOUR
KG SprayCem Texture	T10	White

PRODUCT DESCRIPTION

KG SprayCem Texture refers to a technique used to apply a textured finish to RC wall or plaster surfaces using a spray gun or texture sprayer. This method creates various patterns and textures, adding visual interest and depth to walls. The texture can be fine, heavy mountainous, or heat-cut.

TECHNICAL DATA

BINDER	COATING	DRYING TIME
Ordinary Portland Cement	2 mm to 5 mm	1 to 3 Hours
COVERAGE	WATER RATIO	PACKAGING
1.0 m² to 1.5 m² per kg per coat	40% ± 2%	20kg
STORAGE		
6 Months in original packing		

INSTRUCTION FOR USE

SURFACE FOR PREPARATION

Surfaces to be applied on must be clean, firmly fixed and free from any contamination on the substrate.

APPLICATION

1st Coat: KG SprayCem Texture 2nd Coat: Sealer / Primer

3rd & 4th Coats: Emulsion Paint

FIRE RESISTANCE	SAFETY PRECAUTION
This product is non-combustible.	This product contains cement additives and may cause irritation when in contact with skin or eyes. In case of any contact, wash thoroughly with clean water. If irritation persists, seek immediate medical attention.

DISCLAIMER:

All information contained herein is only intended to give a fair description of the products and their capabilities under such specific test conditions.







