



PRODUCT NAME	CODE	COLOUR
KG Flexi Seal	W100	Black

PRODUCT DESCRIPTION
KG Flexi Seal is a liquid based one part modified polyurethane/ bituminous coating, formulated to form a highly elastic, seamless and crack bridging membrane.

TECHNICAL DATA

DENSITY	PRIMER	ELONGATION AT BREAK
1.1 kg/ litre	Dilute 1 part of KG Flexi Seal with 1 part of water	≥ 100%
TENSILE STRENGTH	CONSUMPTION	COATING
≥ 1.5 N/mm ²	1.6 kg/m ²	2 times at 0.7 kg/m ² per coat
PACKAGING	STORAGE	
25kg	9 Months	

INSTRUCTION FOR USE

SURFACE FOR USE

Substrate must be sound, clean and free from any contamination. Wet the surface prior to application in hot and dry conditions.

MIXING

Mix the product thoroughly using an low speed electric mixer with attached stirrer for 3 - 5 minutes, until a homogeneous mix that is free from lump is achieved.

FIRE RESISTANCE	SAFETY PRECAUTION
-----------------	-------------------

This product is non-combustible.

This product contains cement additives and may cause irritation when in contact with skin or eyes. In case of any contact, wash thoroughly with clean water. If irritation persists, seek immediate medical attention.

DISCLAIMER:

All information contained herein is only intended to give a fair description of the products and their capabilities under such specific test conditions.

However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.



KG-MIX (M) SDN BHD (705033-K)

PT 14498, Persiaran BG Perdana 6, Taman Batu Gajah Perdana, 31550 Pusing, Perak.

Tel: +6(05) 3668323 | Fax: +6(05) 3668363 | Email: inquiry@kgmix.com